

G100E

HYDRAULIC PATCH

SPECIAL FOR OUTDOOR DOORS



GENERAL CHARACTERISTICS

- Grade 3 Certificate (anti corrosion)
- Made of Aisi 304 stainless steel, Grade 3 Certificate
- Working temperatures - 20 °C - + 50 °C
- Special force for opening and closing.
- Withstands high pressures and wind currents
- Certified EN 1154: 1996 / A1: 2002 / AC: 2006 (500,000 Cycles)
- For glass thicknesses from 10 to 15 mm.
- Maximum recommended door weight 115 kg.
- Mechanism provided with 2 closing speeds:
 - 1st speed: approach; acts from 150° to 10°.
 - 2nd speed: closing; acts from 10 to 0
- Provided with retention at 90°.
- Thermo Constate hydraulic fluid. Flash point 160 ° C and freezing point - 40 ° C.

Standard Finishes:

- Bight Inox - satin inox.

Also available in special finishes:

- Lacquered (Black - White - Other), Glitter Gold, Satin Gold, Brass skated, Copper skated. Others consult.

EXCLUSIVE

**1ST HYDRAULIC PERNIO OF THE MARKET,
DESIGNED SPECIFICALLY FOR USE ON EXTERIOR DOORS.**